



US006254105B1

(12) **United States Patent**  
Rinde et al.

(10) Patent No.: **US 6,254,105 B1**  
(45) Date of Patent: **Jul. 3, 2001**

(54) **SEALING SYSTEM FOR ACOUSTIC WAVE TOUCHSCREENS**

(75) Inventors: **James A. Rinde; Barry C. Mathews; Miguel A. Morales; Joel C. Kent**, all of Fremont; **Drew John Loucks**, Los Altos; **John Seymour Mattis**, Sunnyvale; **Jeff Dolln**, Belmont; **Mark W. Ellsworth**, Dublin; **Frank Wasilewski**, Redwood City, all of CA (US)

(73) Assignee: **Elo TouchSystems, Inc.**, Fremont, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/285,407**

(22) Filed: **Apr. 2, 1999**

(51) Int. Cl.<sup>7</sup> ..... **F16J 15/02**

(52) U.S. Cl. .... **277/628; 277/639; 277/650; 345/177**

(58) Field of Search ..... **277/628, 637, 277/639, 650; 345/177; 178/18; 359/513**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

Re. 33,151	1/1990	Adler .
3,020,260	2/1962	Nelson .
4,600,261	7/1986	Debbaut .
4,634,207	1/1987	Debbaut .
4,642,423	2/1987	Adler .
4,644,100	2/1987	Brenner et al. .
4,645,870	2/1987	Adler .
4,700,176	10/1987	Adler .
4,746,914	5/1988	Adler .
4,777,063	10/1988	Dubrow et al. .
4,791,416	12/1988	Adler .
4,816,811	3/1989	Bogatin et al. .
4,825,212	4/1989	Adler et al. .

4,859,996	8/1989	Adler et al. .
4,861,804 *	8/1989	Nakanishi .
4,880,665	11/1989	Adler et al. .
5,005,329 *	4/1991	Schorr .
5,042,821 *	8/1991	Bontly .
5,072,427	12/1991	Knowles .
5,079,300	1/1992	Dubrow et al. .
5,162,618	11/1992	Knowles .
5,177,327	1/1993	Knowles .
5,243,148	9/1993	Knowles .
5,260,521	11/1993	Knowles .
5,329,070	7/1994	Knowles .
5,332,238	7/1994	Borucki .
5,357,057	10/1994	Debbaut .
5,573,077	11/1996	Knowles .
5,591,945	1/1997	Kent .
5,665,809	9/1997	Wojtowicz .
5,708,461	1/1998	Kent .
5,739,479	4/1998	Davis-Cannon et al. .
5,784,054	7/1998	Armstrong et al. .
5,852,433	12/1998	Toda .
5,854,450	12/1998	Kent .

**FOREIGN PATENT DOCUMENTS**

0 740 264 A2	10/1996	(EP) .
WO 98/52184	11/1998	(WO) .

\* cited by examiner


*Primary Examiner*—Lynne H. Browne

*Assistant Examiner*—William L. Miller

(57) **ABSTRACT**

A sealing system for an acoustic touchscreen includes an elongate gel body between the touchscreen and the bezel of a housing onto which the touchscreen is mounted. The elongate gel body forms a seal around the perimeter of the touch-sensitive area of the touchscreen. A stop element controls and limits the amount of compression of the elongate gel body. The resulting seal is highly effective in protecting the unexposed parts of the touchscreen (i.e., areas other than the touch-sensitive area) from contaminants, especially liquid contaminants, at the cost of an acceptably low loss in acoustic signal strength.

**22 Claims, 4 Drawing Sheets**



10, 613, 344